

CORIFONDO (Fondodecor)

PRIMER COAT

DESCRIPTION

CORIFONDO is a vapour-permeable primer coat for unstable and synthetic base surfaces. The product will make dusty base surfaces sound and will give the paint or top coats a more uniform effect due to a more even absorption of water.

For any type of Coridecor topcoat finish, the colour shades and wavy moiré effect will be toned down.

TECHNICAL DATA

Dilution	20 to 50% water
Application	brush
Specific weight	1 kg/l
Coverage	100 to 150 g/m ²

USE

CORIFONDO is applied to a lime or cement base, plasterboard systems, old, powdery mortar, synthetic paints and any unstable base (indoor use).

CORIFONDO is diluted with 20 to 50% water, depending on the absorption of the base. The product must be mixed well prior to use. CORIFONDO is applied by brush in one coat.

COLOURS

CORIFONDO comes in the form of a milky-white product, but can be tinted with Coridecor dyes (Stabilcori).

PACKAGING

1 kg, 5 kg or 25 kg buckets

REMARKS

The current data sheet replaces any previous version.

Our advice and information are given in good faith and depending on the latest developments of our products. We guarantee the consistent quality of our products, but do not accept any liability concerning their application. In any case, we do recommend to consider the type of substrate and the climatic conditions before applying our products or to apply a test surface in order to analyse the suitability of the product for the given substrate.

In case of doubt regarding the substrate, consult our technical service department.