

PLASTELUX

SEALER FOR VENETIAN STUCCO

DESCRIPTION

PLASTELUX is manufactured from lime, linseed oil and special mineral pigments blended for use as a sealer for Venestuk Stucco. By the application of the PLASTELUX, the decorative effects of all the Venetian plasters are enhanced in colour and depth to create a high sheen finish.

The PLASTELUX is resistant to water and washable and can be used in all interior applications including those where condensation is anticipated IN BATHROOMS FOR EXAMPLE

TECHNICAL CHARACTERISTICS

Weight	1650 g/litre.
pH	12
Drying Time	2-3 days depending on weather conditions.
Full cure	1 month.
Coverage	0.3 to 1.0 kgs/m ² dependent upon the substrate (PLASTELUX can be thinned with White Spirit if required)
Packaging	5kg or 25kg tubs.

APPLICATION

PLASTELUX is washable and stain resistant creating an enamel appearance to the Venetian plasters. There is no requirement to wax over the PLASTELUX as its structure makes the finish easy to repair either by overcoating or isolated repair.

Application of PLASTELUX is by special stainless steel trowel or spatula in two or three passes.

NOTE : IT IS RECOMMENDED THAT A SAMPLE OF FINISHED WORKS IS PREPARED FOR APPROVAL PRIOR TO COMMENCEMENT.

REMARKS

The current data sheet replaces any previous version.

Our advice and information are given in good faith and depending on the latest developments of our products. We guarantee the consistent quality of our products, but do not accept any liability concerning their application. In any case, we do recommend to consider the type of substrate and the climatic conditions before applying our products or to apply a test surface in order to analyse the suitability of the product for the given substrate.

In case of doubt regarding the substrate, consult our technical service department.