

# UULA INTO

## PAINT FOR INTERIOR USE

### DESCRIPTION

- semi-gloss
- easy to clean
- quick-drying

UULA INTO is a paint free of solvents for interior use. The binders are natural oils that are recycled. There are no synthetic components.

### TECHNICAL PROPERTIES

|             |  |
|-------------|--|
| Colors      | see color card, other colors on demand   |
| Use         | for all substrates in wood in the interior, like :<br>wood fibre boards, furniture, doors and window frames, also the already painted substrates in acrylic. |
| Coverage    | 7 - 9 m <sup>2</sup> /l  |
| Tools       | brush or roller  |
| Drying time | dry after approx. 30 minutes, ready for next layer after 2 hours   |
| Containers  | 0,9 l, 2,7 l, 9 l  |

### APPLICATION

Not yet painted wood : sand and dust the wood, and then apply 2 layers of UULA INTO.

Already painted wood : strip the poorly adherent layers, and clean and sand the remaining layers.

### REMARKS

The current data sheet replaces any previous version.

Our advice and information are given in good faith and depending on the latest developments of our products. We guarantee the consistent quality of our products, but do not accept any liability concerning their application. In any case, we do recommend to consider the type of substrate and the climatic conditions before applying our products or to apply a test surface in order to analyse the suitability of the product for the given substrate.

In case of doubt regarding the substrate, consult our technical service department.